

Lager und Service							
Größen	Mindest Materialstärke	Schlüsselweite	Bohrloch- ausgang dh 11ø	d1ø	d2ø	Collar height h1	Collar height h
M 2	1,0 mm	5,5 mm	4,5 mm	4,5 mm	4,70 mm	0,9 mm	3,0 mm
M 2,5	1,0 mm	5,5 mm	4,5 mm	4,5 mm	4,70 mm	0,9 mm	3,0 mm
M 3	1,0 mm	5,5 mm	4,5 mm	4,5 mm	4,70 mm	0,9 mm	3,0 mm
M 4	1,0 mm	7,0 mm	5,5 mm	5,5 mm	5,70 mm	0,9 mm	3,2 mm
M 5	1,0 mm	8,0 mm	6,5 mm	6,5 mm	6,75 mm	0,9 mm	4,0 mm
M 6	1,0 mm	10,0 mm	8,0 mm	8,0 mm	8,30 mm	0,9 mm	5,0 mm
M 2,5	1,0 mm	5,5 mm	4,5 mm	4,5 mm	4,70 mm	1,4 mm	3,0 mm
M 3	1,5 mm	5,5 mm	4,5 mm	4,5 mm	4,70 mm	1,4 mm	3,0 mm
M 4	1,5 mm	7,0 mm	5,5 mm	5,5 mm	5,70 mm	1,4 mm	3,2 mm
M 5	1,5 mm	8,0 mm	6,5 mm	6,5 mm	6,75 mm	1,4 mm	4,0 mm
M 6	1,5 mm	10,0 mm	8,0 mm	8,0 mm	8,30 mm	1,4 mm	5,0 mm
M 2,5	1,0 mm	5,5 mm	4,5 mm	4,5 mm	4,70 mm	1,8 mm	3,0 mm
M 3	2,0 mm	5,5 mm	4,5 mm	4,5 mm	4,70 mm	1,8 mm	3,0 mm
M 4	2,0 mm	7,0 mm	5,5 mm	5,5 mm	5,70 mm	1,8 mm	3,2 mm
M 5	2,0 mm	8,0 mm	6,5 mm	6,5 mm	6,75 mm	1,8 mm	4,0 mm
M 6	2,0 mm	10,0 mm	8,0 mm	8,0 mm	8,30 mm	1,8 mm	5,0 mm
M 8	2,0 mm	13,0 mm	10,0 mm	10,0 mm	10,30 mm	1,8 mm	6,5 mm
M 10	2,0 mm	15,0 mm	12,5 mm	12,5 mm	12,85 mm	1,8 mm	8,0 mm
M 12	3,0 mm	17,0 mm	14,5 mm	14,5 mm	14,85 mm	2,8 mm	10,0 mm
M 16	3,0 mm	22,0 mm	18,5 mm	18,5 mm	18,85 mm	2,4 mm	13,0 mm
M 20	4,0 mm	27,0 mm	23,0 mm	23,0 mm	23,40 mm	3,8 mm	16,0 mm

